

polyPANEL is made from 10mm rigid PVC with a decorative face. All panels have a tongue and grooved long edge


SIZE/WEIGHT 2400 x 1000 x 10mm/ 11kg

PANELS/PACK 2 (individual panels available at a supplementary cost)


COLOURS Please refer to brochure

ACCESSORIES polyPANEL PVC edge profiles 2.4m long are available in three profiles and three finishes: Silver, White and black.


Type U End Cap
External Corner



Type V
Internal Corner



Type W
External Corner



CLEANING

The panels should be cleaned using warm water and a non abrasive mild detergent (not bleach). Scouring products or powders should not be used.

FIRE & SMOKE RATING

polyPANEL carries a Class 3 classification, when tested for heat and smoke release in accordance with AS/NZS 3837:1998. The panels have an average specific extinction area of 6 l.8m²/kg. No specific fire-fighting instructions are required.

THERMAL PROPERTIES

polyPANEL can with-stand surface temperatures / heat of up to 60°C before any discolouration or warping of the PVC.

CHEMICAL RESISTANCE

PVC is resistant to caustics, mineral oil, and foodstuffs like milk and coffee etc.

IMPACT RESISTANCE

Test EN13245-1:2004: pass: 5 joule at 23degrees centigrade.

SCALE FORMATION

Low susceptibility to hard water. Standard scale remover can be used on any scale build-up.